



The H135PP is the "foundation" of the Hydra 985. With its self contained power pack the unit features hydraulic loading and self-maneuverability in the yard and at the job-site. Its rugged, open yoke, rigid frame give it the strength required for tough use, even in off-road applications.

The hydraulically driven, power idler wheel with its heavy-duty pneumatic tire turns the unit into a piece of self maneuvering machinery. The unit can work independently of the truck to easily maneuver in crowded reel yards or tight job locations such as alleys, parking lots, sidewalks or narrow streets. One man can put the unit where it's needed without difficult truck movements.



Designers & Manufacturers of Line Construction





Shown with optional outriggers and hydraulic retriever.

SPECIFICATIONS

Reel Capacity: Single, 108"

DIAx56" Wide

Axle: Stub Spindle, 10 hole single

Brakes: 16x5 Air Brakes w/ABS (STD), 16x5 12v Electric

(Optional)

Tires: 14/80R20 18PR (STD)

18,000 GAWR

Engine: Air-Cooled, 9HP, 12V Starter, Flywheel alternator Hydraulics: Open-center, 4 GPM,

2000 PSI, 10 gal. Reservoir, Wire mesh suction filter, four section valve with pressure relief.

- Hydraulic reel lifts
- · Hydraulic actuated idler wheel 2 1/2 Reel mandrel w/centering cones and locking collars
- Cadmium plated, quick release mechanical jackstands
- · Built-in storage boxes
- · Safety chain
- · Wheel chocks
- Mudflaps
- · All required lights (all lights are sealed beam, recessed and shock mounted).

H11315 PP

Power Pack features a 9HP air cooled engine with 12V starter. Open center hydraulic system features 4 GPM, 2000 PSI pump, 10 gallon reservoir with suction filter and four section control valve with pressure relief. The engine, pump, battery and reservoir are mounted low in the frame to guard against impact in rough terrain applications.

Multiple-pocket reel lifts load and carry reels 50" to 108" in diameter up to 56" wide/ Lifting capacity is 20,000 pounds. Mechanical locks and stabilizers relieve all strain from the hydraulic system when towing. Quick release mechanical jack-stands provide a stable platform for loading and pay-out operations.



The H135PP is a modular approach to line construction equipment. A Power Unit can be added to the H135PP to create full cable pulling capabilities. All power unit mounting rails and cylinder anchors are incorporated into the H135PP. So, as your requirements grow, the H135PP can grow with them. This system reduces equipment obsolescence and future capital expenditures. Above is an example of one conversion possibility – the H135PP can become the Hydra 985. The Hydra 985 is our diesel powered 24,000 lb. line pull cable reel unit.



In order that product improvement may be introduced at any time, specifications are subject to change without notice.



P.O. BOX 405 3800 EAGLE LOOP ODELL, OR 97044 TEL (541) 354-1001 FAX (541) 354-1080 www.hoggdavis.com DISTRIBUTED BY