

# T150

**Cable  
Reel  
Dolly**



**HOGG & DAVIS, Inc.**

Designers and  
Manufacturers  
of Line  
Construction  
Equipment

**RUGGED DEPENDABILITY**

# T150

# Cable Reel Dolly



The Hogg & Davis, inc. Model T150 Cable Reel Dolly is an open yoke unit designed for low center of gravity reel hauling. It offers operating ease and simple maintenance. The 4" x 6", 1/2" wall tubular frame, super structure and heavy duty fenders and panels are integrated into a structurally strong and rigid unit designed for years of rugged service. It is backed by years of experience, knowledge and quality which Hogg & Davis, inc. is known worldwide for.

## Power Pack Unit

13 HP Air cooled Honda engine is mounted on a 15 gallon hydraulic reservoir with submerged hydraulic pump. Electric start with rope pull back up. Valve bank for operation of Mandrel Racks, Idler wheel and optional retriever arm.



## General Specifications

Reel Capacity: Up to 108" dia x 60" wide
Hydraulic reel lifts (Double acting cylinders)
Nickle plated, Quick release Jackstands
20,000 lb. stub axles with machined attachment plates
Full airbrakes with ABS
315/80/R22.5 tires with 22.5x9, 10 lug bud rims
Double shock mounted LED lights with pigtail connectors
2 1/2" inch heat treated reel shaft with centering cones, locking collars and Nylatron® bearings
3" x 12" Bearing mounted idler wheel
Hydraulically raised drawbar
Adjustable pintle eye with dual safety chains
12" x 16" x 22.5" Lockable toolbox (Optional)
Retriever arm (Optional)
Reel Brake- Retriever mounted (Optional)
Reel Brake- Mandrel bar mounted (Optional)

## Dimensions

Length: 164" (4165mm)
Width: 96" (2438mm)
Height: 61" (1549mm)
Approx weight: 3,800 lbs.
GVWR: 18,900 lbs.
Gawr: 18,180 lbs.
Approx tongue weight: 550 lbs.
Approx tongue weight w/ retriever: 850 lbs.



## Optional Retriever

The optional Retriever is designed to provide quick and efficient retrieval of wire and cable when used in conjunction with the T150 Cable Reel Dolly. Capable of developing 2,000 lbs bare drum line pull, the retriever is ideal for winding tails, open wire, dropped spans, etc.

Product improvements may be introduced at anytime, specifications are subject to change without notice.



P.O.Box 405  
3800 Eagle Loop  
Odell, Oregon 97044  
TEL(541)354-1001  
FAX(541)354-1080

Visit us at  
[www.hoggdavis.com](http://www.hoggdavis.com)